TAU User's Guide



TAU User's Guide

version 2.7 Beta Release 1

Department of Computer and Information Science,
University of Oregon, OR
Advanced Computing Laboratory, LANL, NM
Research Centre Jülich, ZAM, Germany

http://www.acl.lanl.gov/tau

Copyright © 1997-99

Department of Computer and Information Science, University of Oregon
Advanced Computing Laboratory, LANL, NM
Research Centre Jülich, ZAM, Germany

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of University of Oregon (UO) Research Centre Jülich, (ZAM) and Los Alamos National Laboratory (LANL) not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. The University of Oregon, ZAM and LANL make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

UO, ZAM AND LANL DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE UNIVERSITY OF OREGON, ZAM OR LANL BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright © 1999.

All rights reserved.

Contents

CHAPTER 1 *Installation* ***1***

Installing TAU **2**
Examples: **5**
Platforms Supported **7**
Software Requirements **8**

CHAPTER 2 *Compiling* ***9***

TAU stub Makefile **10**
Enabling and Disabling the Instrumentation **12**
Using TAU with MPI **12**
Environment Variables **13**

CHAPTER 3 *Instrumentation* ***15***

Automatic Instrumentation of C++ sources **16**
C++ Instrumentation API **18**
TAU Mapping API **27**
C Instrumentation API **32**
Fortran90 Instrumentation API **33**
Summary **39**

CHAPTER 4 *Profiling* ***41***

Running the application **42**
Using Hardware Performance Counters **42**
pprof **45**
racy **46**

CHAPTER 5 *Tracing* ***53***

Generating Event Traces **54**
Vampir: Visualizing TAU traces **55**

CHAPTER 6 *Summary* ***63***

Software Availability **64**
Acknowledgements **64**

CHAPTER 1

Installation

TAU (Tuning and Analysis Utilities) is a portable profiling and tracing toolkit for performance analysis of parallel programs written in C++, C, and Fortran. The model that TAU uses to profile parallel, multi-threaded programs maintains performance data for each thread, context, and node in use by an application. The profiling instrumentation needed to implement the model captures data for C++ functions, methods, basic blocks, and statement execution at these levels. All C++ language features are supported in the TAU profiling instrumentation including templates and namespaces, which is available through an API at the library or application level. The API also provides selection of profiling groups for organizing and controlling instrumentation. The instrumentation can be inserted in the source code using an automatic instrumentor tool based on the Program Database Toolkit, or manually using the instrumentation API.

TAU's profile visualization tool, racy, provides graphical displays of all the performance analysis results, in aggregate and single node/context/thread forms. The user can quickly identify sources of performance bottlenecks in the application using the graphical interface. In addition, TAU can generate event traces that can be displayed with the Vampir trace visualization tool.

This chapter discusses installation of the TAU portable profiling package.

Installing TAU

After uncompressing and untarring tau, the user needs to configure, compile and install the package. This is done by invoking:

```
% ./configure
% make install
```

TAU is configured by running the **configure** script with appropriate options that select the profiling and tracing components that are used to build the TAU library. The following command-line options are available to configure:

-prefix=<directory>

Specifies the destination directory where the header, library and binary files are copied. By default, these are copied to subdirectories <arch>/bin and <arch>/lib in the TAU root directory.

-arch=<architecture>

Specifies the architecture. If the user does not specify this option, configure determines the architecture. For SGI, the user can specify either of sgi32, sgin32 or sgi64 for 32, n32 or 64 bit compilation modes respectively. The files are installed in the <architecture>/bin and <architecture>/lib directories.

-c++=<C++ compiler>

Specifies the name of the C++ compiler. Supported C++ compilers include KCC (from KAI), CC, g++ (from GNU), FCC (from Fujitsu) and pgCC (from PGI).

-cc=<C Compiler>

Specifies the name of the C compiler. Supported C compilers include cc, gcc (from GNU), pgcc (from PGI), fcc (from Fujitsu) and KCC (from KAI).

-pthread

Specifies pthread as the thread package to be used. In the default mode, no thread package is used.

-tulipthread=<directory>

Specifies Tulip threads (HPC++) as the threads package to be used as well as the location of the root directory where the package is installed.
[URL: `http://www.acl.lanl.gov/tulip`]

-tulipthread=<directory> -smarts

Specifies SMARTS (Shared Memory Asynchronous Runtime System) as the threads package to be used. <directory> gives the location of the SMARTS root directory. [URL: `http://www.acl.lanl.gov/smarts`]

-pdt=<directory>

Specifies the location of the installed PDT (Program Database Toolkit) root directory. PDT is used to build **tau_instrumentor**, a C++ instrumentation program that automatically inserts TAU annotations in the source code.
[URL: `http://www.acl.lanl.gov/pdtoolkit`]

-pcl=<directory>

Specifies the location of the installed PCL (Performance Counter Library) root directory. PCL provides a common interface to access hardware performance counters on modern microprocessors. The library supports Sun UltraSparc I/II, PowerPC 604e under AIX, MIPS R10000/12000 under IRIX, Compaq Alpha 21164, 21264 under Tru64Unix and Cray Unicos (T3E) and the Intel Pentium family of microprocessors under Linux. This option specifies the use of hardware performance counters for profiling (instead of time). See the section “Using Hardware Performance Counters” in Chapter 4 for details regarding its usage.
[URL : `http://www.fz-juelich.de/zam/PCL`]

-jdk=<directory>

Specifies the location of the installed Java 2 Development Kit (JDK1.2+) root directory. TAU can profile or trace Java applications without any modifications to the source code, byte-code or the Java virtual machine.

-mpiinc=<dir>

Specifies the directory where mpi header files reside (such as mpi.h and mpif.h). This option also generates the TAU MPI wrapper library that instruments MPI routines using the MPI Profiling Interface. See the examples/NPB2.3/config/make.def file for its usage with Fortran and MPI programs.
[URL: `http://www-unix.mcs.anl.gov/mpi/`]

-mpilib=<dir>

Specifies the directory where mpi library files reside. This option should be used in conjunction with the -mpiinc=<dir> option to generate the TAU MPI wrapper library.

-PROFILE

This is the default option; it specifies summary profile files to be generated at the end of execution. Profiling generates aggregate statistics (such as the total time spent in routines and statements), and can be used in conjunction with the profile browser **racy** to analyse the performance. Wallclock time is used for profiling program entities.

-PROFILESTATS

Specifies the calculation of additional statistics, such as the standard deviation of the exclusive time/counts spent in each profiled block. This option is an extension of -PROFILE, the default profiling option.

-PROFILECOUNTERS

Specifies use of hardware performance counters for profiling under IRIX using the SGI R10000 perfex counter access interface. The use of this option is deprecated in favor of the -pcl=<dir> option described above.

-SGITIMERS

Specifies use of the free running nano-second resolution on-chip timer on the R10000. This timer has a lower overhead than the default timer on SGI, and is recommended for SGIs.

-TRACE

Generates event-trace logs, rather than summary profiles. Traces show when and where an event occurred, in terms of the location in the source code and the process that executed it. Traces can be merged and converted using **tau_merge** and **tau_convert** utilities respectively, and visualized using Vampir, a commercial trace visualization tool. [URL `http://www.pallas.de`]

-noex

Specifies that no exceptions be used while compiling the library. This is relevant for C++.

-useropt=<options-list>

Specifies additional user options such as -g or -I. For multiple options, the options list should be enclosed in a single quote. For example

```
%./configure -useropt='-g -I/usr/local/stl'
```

-help

Lists all the available configure options and quits.

Examples:

a) Install TAU using KCC on SGI, with trace and profile options:

```
%./configure -c++=KCC -SGITIMERS -arch=sgi64 -TRACE
     -PROFILE -prefix=/usr/local/packages/tau
```

b) Installing TAU with Java

```
% ./configure -c++=g++ -jdk=/usr/local/packages/jdk1.2
% make install
% set path=($path <taudir>/<tauarch>/bin)
% setenv LD_LIBRARY_PATH $LD_LIBRARY_PATH:<taudir>/
<tauarch>/lib
% cd examples/java/pi
% java -XrunTAU Pi 200000
% racy
```

c) For installing **TAU** with **POOMA**:

1. Configure PDT

```
% cd /usr/local/packages/pdtoolkit-1.0
[FOR SGI]
% configure -KCC -arch=IRIX64
[FOR LINUX PCs]
% configure -KCC
```

2. Configure TAU

```
% cd /usr/local/packages/tau-2.6
[FOR SGI]
% ./configure -arch=sgi64 -pdt=/usr/local/packages/
    pdtoolkit-1.0 -c++=KCC -tulipthread=/usr/local/
    packages/smarts-1.0 -smarts -SGITIMERS
% set path=($path /usr/local/packages/tau-2.6/sgi64/
    bin)
[FOR LINUX PCs]
% ./configure -arch=linux -pdt=/usr/local/packages/
    pdtoolkit-1.0 -c++=KCC -tulipthread=/usr/local/
    packages/smarts-1.0 -smarts
% set path=($path /usr/local/packages/tau-2.6/linux/
    bin)
% make install
```

3. Configure SMARTS

```
% cd /usr/local/packages/smarts-1.0
[FOR SGI]
% configure --with-arch=iris4d --prefix /usr/local/
    packages/smarts-1.0 --with-taudir=/usr/local/pack-
    ages/tau-2.6 --enable-64bit --enable-profile
[FOR LINUX PCs]
% configure --with-arch=i386-linux --prefix /usr/local/
    packages/smarts-1.0 --with-taudir=/usr/local/pack-
    ages/tau-2.6 --enable-profile
% make
% make install
```

4. Configure Pooma II

```
% setenv TAUDIR     /usr/local/packages/tau-2.6
% setenv PDTDIR     /usr/local/packages/pdtoolkit-1.0
```

```
% setenv SMARTSDIR  /usr/local/packages/smarts-1.0
[FOR SGI]
% ./configure --arch SGI64KCC --suite PP --parallel --
    profile --opt
[FOR LINUX PCs]
% ./configure --arch LINUXKCC --suite PP --parallel --
    profile --opt
% setenv SUITE PP
% make
% cd examples/Solvers/SimpleJacobi
% make
% cd PP
% SimpleJacobi
% pprof; racy;
```

Platforms Supported

TAU has been tested on the following platforms:

1. SGI

On IRIX 6.x based systems, including Indy, Power Challenge, Onyx, Onyx2 and Origin 200 and 2000 Series, CC 7.2+, KAI [URL: `http://www.kai.com`] KCC and g++/egcs [URL: `http://www.gnu.org`] compilers are supported.

2. LINUX PCs

On Linux based Intel x86 PC clusters, KAI KCC, g++, egcs (GNU), pgCC (PGI) [URL:http://www.pgroup.com], FCC (Fujitsu) [URL: `http://www.tools.fujitsu.com/linux/index.shtml`] compilers have been tested. Versions of g++ prior to 2.8.1 need an additional -useropt=-fguiding-decls to be added to the list of configure options. Among the GNU versions, we recommend using gcc-2.95 g++.

3. Sun Solaris

KAI KCC and GNU g++ work with TAU.

4. IBM AIX

On IBM SP2 and AIX systems, KAI KCC and g++ compilers work with TAU.

5. HP HP-UX

On HP PA-RISC systems, g++ can be used.

6. Compaq (DEC Alpha workstations)

On Compaq (DEC) Alpha workstations running Digital Unix, g++ may be used with TAU.

7. LINUX Compaq (DEC Alpha 21164) clusters

On Linux based Alpha workstation clusters, g++ may be used with TAU.

8. Cray T3E

On Cray, KAI KCC and Cray CC compilers have been tested with TAU.

TAU has been tested with JDK 1.2 on Solaris and Linux. On Solaris, we needed to disable support for the JIT compiler by specifying -Djava.compiler= on the java commandline along with -XrunTAU. On Linux, it worked with or without the JIT compiler.

TAU may work with minor modifications on other platforms.

Software Requirements

1. Tcl/Tk

TAU's GUI **racy** requires Tcl/Tk 7.4/4.0 or better (8.x is recommended). Tcl/Tk can be downloaded from URL: `http://www.scriptics.com` as freeware.

2. Xauth

The display must be secure to run racy, the profile browser. Xauthority -- not `xhost+` should be used for secure (authentication based) interaction between the X client and the servers. Refer to the TAU FAQ
URL: `http://www.acl.lanl.gov/tau/docs/faq.html#security` for instructions. Contact your system administrator if your X-server is not configured for generating Xauth cookies.

CHAPTER 2

Compiling

This chapter explains compilation options to enable profiling or tracing.

TAU stub Makefile

TAU configuration generates a Makefile stub as well as a library. The Makefile name has the form `Makefile.tau-<options>`, the library name the form `libtau-<options>.a`. For example,

```
%./configure -TRACE -c++=KCC -arch=sgin32
```

generates

```
Makefile.tau-trace-kcc  libtau-trace-kcc.a
```

in `tau-2.x/sgin32/lib`

Using different configuration options, several modular libraries can be built and co-exist even in the same architecture. To choose a particular version of the library, the corresponding Makefile stub must be included in the application Makefile. The stub Makefile defines the following variables:

- `TAU_CXX` for the C++ compiler
- `TAU_CC` for the C compiler
- `TAU_INCLUDE` for the include directories
- `TAU_DEFS` for the defines on the command-line
- `TAU_LIBS` for the TAU library
- `TAU_MPI_INCLUDE` for the directory where MPI header files reside
- `TAU_MPI_LIBS` for the TAU MPI library with the mpi libraries for C/C++
- `TAU_MPI_FLIBS` for the TAU MPI library with mpi libraries for Fortran
- `TAU_FORTRANLIBS` for additional fortran libraries for linking with C++
- `TAU_DISABLE` for the default TAU stub library for Fortran, and
- `USER_OPT` for any user defined options specified during configuration

A typical makefile that uses these Makefile variables is shown below:

```
TAUROOTDIR      = /usr/local/packages/tau-2.x
include $(TAUROOTDIR)/sgin32/lib/Makefile.tau-trace-kcc
CXX             = $(TAU_CXX)
CC              = $(TAU_CC)
CFLAGS          = $(TAU_INCLUDE) $(TAU_DEFS)
LIBS            = $(TAU_LIBS) -lmpi
LDFLAGS         = $(USER_OPT)
MAKEFILE        = Makefile
PRINT           = pr
RM              = /bin/rm -f
TARGET          = matrix
EXTRAOBJS       =
################################################
all:            $(TARGET)
install:        $(TARGET)
$(TARGET):      $(TARGET).o
        $(CXX) $(LDFLAGS) $(TARGET).o -o $@ $(LIBS)
$(TARGET).o : $(TARGET).cpp
        $(CXX) $(CFLAGS) -c $(TARGET).cpp
clean:
        $(RM) $(TARGET).o $(TARGET)
################################################
```

To use a different configuration, simply change the included makefile to some other. For example, for

```
% ./configure -pthread -arch=sgi64
```

substitute

```
include $(TAUROOTDIR)/sgi64/lib/Makefile.tau-pthread
```

in the makefile above. Also,

```
$(TAUROOTDIR)/include/Makefile
```

points to the most recently configured version of the library.

Enabling and Disabling the Instrumentation

Using the TAU stub makefile variable `TAU_DEFS` while compiling C++ and C source code enables profiling (or tracing) instrumentation and generates the data files. To disable the instrumentation, `TAU_DEFS` should not be used. In its absence, all the TAU profiling macros defined in the source code for instrumentation purposes are automatically defined to null (the default behavior). The instrumentation can be retained in the source code, since it has no overhead when it is disabled.

For Fortran however, the instrumentation can be disabled in the program by using on the link command line, the TAU stub makefile variable `TAU_DISABLE`. This points to a library that contains empty TAU instrumentation routines.

Using TAU with MPI

TAU MPI wrapper library (libTauMpi.a) uses the MPI Profiling Interface for instrumentation. To use the library,

1. Configure TAU with -mpiinc=<dir> and -mpilib=<dir> command-line options that specify the location of MPI header files and the directory where MPI libraries reside. For example:

```
% ./configure -mpiinc=/usr/local/packages/mpich/
include -mpilib=/usr/local/packages/mpich/lib/LINUX/
ch_p4 -c++=KCC -cc=cc
```

2. Include the TAU stub Makefile generated in the application makefile.

```
TAUROOTDIR=/usr/local/packages/tau2
include $(TAUROOTDIR)/i386_linux/Makefile.tau-kcc
```

3. Use the Makefile variables `$(TAU_MPI_LIBS)` for C/C++ applications and `$(TAU_MPI_FLIBS)` for Fortran 90 applications, to specify the TAU MPI libraries before the `$(TAU_LIBS)` in the link command line. Also, use `$(TAU_MPI_INCLUDE)` in the compiler command line to specifies the MPI include directory to be used. For example:

```
CXX      = $(TAU_CXX)
CFLAGS   = $(TAU_INCLUDE) $(TAU_DEFS) $(TAU_MPI_INCLUDE)
LIBS     = $(TAU_MPI_LIBS) $(TAU_LIBS)
```

4. Compile and run the MPI application as usual to generate the performance data.

Environment Variables

When the program has been compiled, it can be executed as it normally would be (for example, using mpirun for an MPI task). TAU generates profile data files or trace files in the current working directory. To better manage different experiments, set the environment variables

- **`PROFILEDIR`** to name the directory that should contain the profile data files and
- **`TRACEDIR`** the directory where event traces should be stored.
- `LD_LIBRARY_PATH` should include the <tauroot>/<tauarch>/lib directory if TAU is used with JAVA 2 (using the -jdk=<dir> configuration option).

For example:

```
% make
% setenv TRACEDIR /users/foo/tracedata/experiment1
% mpirun -np 4 matrix

For Java:
% cd examples/java/pi
% setenv LD_LIBRARY_PATH $LD_LIBRARY_PATH:/home/tau/
solaris2/lib
% java -XrunTAU Pi
or
% java -XrunTAU -Djava.compiler=  Pi
To disable the JIT compiler.
```

NOTE: TAU also uses the environment variable **`PCL_EVENT`** to specify the hardware performance counter to be used when -pcl=<dir> configure option is used. See section “Using Harware Performance Counters” in Chapter 4 for further details.

CHAPTER 3

Instrumentation

For TAU instrumentation, macros must be added to the source code to identify routine transitions. It can be done automatically using the C++ instrumentor - **tau_instrumentor**, based on the Program Database Toolkit, or manually using the instrumentation API (Application Programmers Interface).

Automatic Instrumentation of C++ sources

tau_instrumentor inserts TAU instrumention macros in C++ source code using PDT [URL: `http://www.acl.lanl.gov/pdtoolkit`].

1. Install pdtoolkit. Refer to the README file in the PDT directory.
   ```
   % ./configure -arch=IRIX64 -KCC
   ```
2. Install TAU using the -pdt configuration option.
   ```
   % ./configure -pdt=/usr/local/packages/pdtoolkit-1.0 -c++=KCC -arch=sgi64 -SGITIMERS
   % make install
   ```
3. Modify the makefile to invoke cxxparse from PDT which generates a program database file (.pdb) that contains program entities (such as routine locations) and tau_instrumentor that uses the .pdb file and the C++ source code to generate an instrumented version of the source code. See examples/autoinstrument/Makefile. For example, the original makefile

```
CXX             = CC
CFLAGS          =
LIBS            = -lm
TARGET          = klargest
###############################################
# Original Rules
###############################################
all:            $(TARGET)
$(TARGET):      $(TARGET).o
        $(CXX) $(LDFLAGS) $(TARGET).o -o $@ $(LIBS)
$(TARGET).o : $(TARGET).cpp
        $(CXX) $(CFLAGS) -c $(TARGET).cpp
clean:
        $(RM) $(TARGET).o $(TARGET)
###############################################
```

is modified as follows. Some changes are shown in bold font.

```
TAUROOTDIR      = /usr/local/packages/tau2/
include $(TAUROOTDIR)/sgi64/Makefile.tau
CXX             = $(TAU_CXX)
CFLAGS          = $(TAU_INCLUDES) $(TAU_DEFS)
LIBS            = -lm $(TAU_LIBS)
PDTPARSE =$(PDTDIR)/$(CONFIG_ARCH)/bin/cxxparse
TAUINSTR =$(TAUDIR)/$(CONFIG_ARCH)/bin/tau_instrumentor
```

```
##############################################
# Modified Rules
##############################################

all:    $(TARGET) $(PDTPARSE) $(TAUINSTR)

$(TARGET): $(TARGET).o
      $(CXX) $(LDFLAGS) $(TARGET).o -o $@ $(LIBS)

# Use the instrumented source code to generate the
object code
$(TARGET).o : $(TARGET).inst.cpp
       $(CXX) -c $(CFLAGS) $(TARGET).inst.cpp  -o $(TAR-
GET).o

# Generate the instrumented source from the original
source and the pdb file
$(TARGET).inst.cpp : $(TARGET).pdb $(TARGET).cpp
$(TAUINSTR)
       $(TAUINSTR) $(TARGET).pdb $(TARGET).cpp -o $(TAR-
GET).inst.cpp

# Parse the source file to generate the pdb file
$(TARGET).pdb : $(PDTPARSE) $(TARGET).cpp
        $(PDTPARSE) $(TARGET).cpp $(CFLAGS)

clean:
        $(RM) $(TARGET).o $(TARGET).inst.cpp $(TARGET)
$(TARGET).pdb
##############################################
$(PDTPARSE):
  @echo "*************************************"
   @echo "Download and Install Program Database Toolkit "
   @echo "ERROR: Cannot find $(PDTPARSE)"
   @echo "*************************************"
$(TAUINSTR):
   @echo "*************************************"
   @echo "Configure TAU with -pdt=<dir> option to use"
   @echo "C++ instrumentation with PDT"
   @echo "ERROR: Cannot find $(TAUINSTR)"
   @echo "*************************************"
```

4. Compile and execute the application.

The user may also opt to manually insert TAU macros in the source code using the C++ instrumentation API. The following section describes this API in detail.

C++ Instrumentation API

The API is a set of macros that can be inserted in the C++ source code. An extension of the same API is available to instrument C and Fortran sources. This is discussed later.

At the beginning of each instrumented source file, include the following header

```
#include <Profile/Profiler.h>
```

TAU_PROFILE(function_name, type, group);

```
Arguments:
char * function_name or string& function_name
char *type_name or string& type
TauGroup_t group
```

With `TAU_PROFILE`, the function `function_name` is profiled. `TAU_PROFILE` identifies the function uniquely by the combination of its name and type parameters. Each function is also associated with the group to which it belongs. This information can selectively enable or disable instrumentation in a set of profile groups. A function that belongs to the `TAU_DEFAULT` group is always profiled. Other user defined groups are `TAU_USER`, `TAU_USER1`, `TAU_USER2`, `TAU_USER3`, `TAU_USER4`. The top level function in any thread must be profiled using the TAU_DEFAULT group. For details on using selective instrumentation, please refer to the section “Running the application” in Chapter 4.

example:

```
int main(int argc, char **argv)
{
TAU_PROFILE("main()","int (int, char **)",TAU_DEFAULT);
```

string& CT(variable);

```
Arguments:
<type> variable
```

The CT macro returns the runtime type information string of a variable. This is useful in constructing the type parameter of the TAU_PROFILE macro. For templates, the type information can be constructed using the type of the return and the type of each of the arguments (parameters) of the template. The example in the following macro will clarify this.

TAU_TYPE_STRING(variable, type_string);

```
Arguments:
string & variable;
string &  type_string;
```

This macro assigns the string constructed in type_string to the variable. The + operator and the CT macro can be used to construct the type string of an object. This is useful in identifying templates uniquely, as shown below.

Example:

```
template<class PLayout>
ostream& operator<<(ostream& out, const Particle-
Base<PLayout>& P) {
  TAU_TYPE_STRING(taustr, "ostream (ostream, " + CT(P) +
     " )" );
   TAU_PROFILE("operator<<()", taustr, TAU_PARTICLE |
     TAU_IO);
...
}
```

When PLayout is instantiated with "UniformCartesian<3U, double>", this generates the unique template name :

```
"operator<<() ostream const ParticleBase<UniformCarte-
     sian<3U, double> > )"
```

The following example illustrates the usage of the CT macro to extract the name of the class associated with the given object using CT(*this);

```
template<class PLayout>
unsigned ParticleBase<PLayout>::GetMessage(Message&
    msg, int node) {
  TAU_TYPE_STRING(taustr, CT(*this) + " unsigned (Mes-
    sage, int)");
  TAU_PROFILE("ParticleBase::GetMessage()", taustr,
    TAU_PARTICLE);
...
}
```

When PLayout is instantiated with "UniformCartesian<3U, double>", this generates the unique template name:

```
"ParticleBase::GetMessage() ParticleBase<UniformCarte-
    sian<3U, double> > unsigned (Message, int)"
```

TAU_PROFILE_TIMER(timer, name, type, group);

```
Arguments:
Profiler timer;
char * name or string & name;
char * type or string & type;
TauGroup_t group;
```

With TAU_PROFILE_TIMER, a group of one or more statements is profiled. This macro has a timer variable as its first argument, and then strings for name and type, as described earlier. It associates the timer to the profile group specified in the last parameter.

```
Example:
template< class T, unsigned Dim >
void BareField<T,Dim>::fillGuardCells(bool reallyFill)
{
  // profiling macros
  TAU_TYPE_STRING(taustr, CT(*this) + " void (bool)" );
```

```
TAU_PROFILE("BareField::fillGuardCells()", taustr,
   TAU_FIELD);

TAU_PROFILE_TIMER(sendtimer, "fillGuardCells-send",
                  taustr, TAU_FIELD);
TAU_PROFILE_TIMER(localstimer, "fillGuardCells-
   locals", taustr, TAU_FIELD);
```

TAU_PROFILE_START(timer);

```
Arguments:
Profiler timer;
```

The macro `TAU_PROFILE_START` starts the timer associated with the set of statements that are to be profiled.

TAU_PROFILE_STOP(timer);

```
Arguments:
Profiler timer;
```

The macro `TAU_PROFILE_STOP` stops the timer.

It is important to note that timers can be nested, but not overlapping. TAU detects programming errors that lead to such overlaps at runtime, and prints a warning message.

Example:

```
template< class T, unsigned Dim >
void BareField<T,Dim>::fillGuardCells(bool reallyFill)
```

```
{
  // profiling macros
  TAU_TYPE_STRING(taustr, CT(*this) + " void (bool)" );
  TAU_PROFILE("BareField::fillGuardCells()", taustr,
    TAU_FIELD);

  TAU_PROFILE_TIMER(sendtimer, "fillGuardCells-send",
                    taustr, TAU_FIELD);
  TAU_PROFILE_TIMER(localstimer, "fillGuardCells-
    locals", taustr, TAU_FIELD);
// ...
  TAU_PROFILE_START(sendtimer);
    // set up messages to be sent
    Message** mess = new Message*[nprocs];
    int iproc;
    for (iproc=0; iproc<nprocs; ++iproc) {
      mess[iproc] = NULL;
      recvmsg[iproc] = false; }//... other code
  TAU_PROFILE_STOP(sendtimer);
  ...
}
```

TAU_PROFILE_STMT(statement);

```
Arguments:
statement;
```

TAU_PROFILE_STMT declares a variable that is used only during profiling or for execution of a statement that takes place only when the instrumentation is active. When instrumentation is inactive (i.e., when profiling and tracing are turned off as described in Chapter 2), all macros are defined as null.

Example:

```
TAU_PROFILE_STMT(T obj;); // T is a template parameter)
TAU_TYPE_STRING(str, "void () " + CT(obj) );
```

TAU_PROFILE_INIT(argc, argv);

```
Arguments:
int argc;
char **argv;
```

TAU_PROFILE_INIT parses the command-line arguments for the names of profile groups that are to be selectively enabled for instrumentation. By default, i.e., if this macro is not used, functions belonging to all profile groups are enabled.

Example:

```
int main(int argc, char **argv){
  TAU_PROFILE("main()", "int (int, char **)",
     TAU_DEFAULT);
  TAU_PROFILE_INIT(argc, argv);
...
}
```

TAU_PROFILE_SET_NODE(myNode);

```
Arguments:
int myNode;
```

The TAU_PROFILE_SET_NODE macro sets the node identifier of the executing task for profiling and tracing. TAU uses the HPC++ model of computation, where the tasks are identified using node, context and thread. The profile data files generated will accordingly be named
profile.<node>.<context>.<thread>.

TAU_PROFILE_SET_CONTEXT(myContext);

```
Argument:
int myContext;
```

TAU_PROFILE_SET_CONTEXT sets the context parameter of the executing task for profiling and tracing purposes. This is similar to setting the node parameter with TAU_PROFILE_SET_NODE.

TAU_PROFILE_REGISTER_THREAD();

To register a thread with the profiling system, invoke the TAU_PROFILE_REGISTER_THREAD macro in the run method of the thread prior to executing any other TAU macro. This sets up thread identifiers that are later used by the instrumentation system.

TAU_PROFILE_EXIT(message);

```
Argument:
const char * message;
```

TAU_PROFILE_EXIT should be called prior to an error exit from the program so that any profiles or event traces can be dumped to disk before quitting.

Example:

```
if ((ret = open(...)) < 0) {
  TAU_PROFILE_EXIT("ERROR in opening a file");
  perror("open() failed");
  exit(1);
}
```

TAU_REGISTER_EVENT(variable, event_name);

```
Arguments:
TauUserEvent & variable;
char * event_name;
```

TAU can profile user-defined events using TAU_REGISTER_EVENT. The meaning of the event is determined by the user.

TAU_EVENT(variable, value);

```
Arguments: TauUserEvent & variable;
double value;
```

TAU_EVENT associates a value with some user-defined event. When the event is triggered and this macro is executed, TAU maintains statistics, such as maximum, minimum values, standard deviation, number of samples, etc. for tracking this event.

Example:

```
int ArraySend(int arrayid)
{
  TAU_REGISTER_EVENT(taumsgsize, "Size of message asso-
     ciated with Arrays");
  int size = GetArraySize(arrayid);
  TAU_EVENT(size);
// ...
}
```

TAU_REPORT_STATISTICS();

TAU_REPORT_STATISTICS prints the aggregate statistics of user events across all threads in each node. Typically, this should be called just before the main thread exits.

TAU_REPORT_THREAD_STATISTICS();

TAU_REPORT_THREAD_STATISTICS prints the aggregate, as well as per thread user event statistics. Typically, this should be called just before the main thread exits.

TAU_TRACE_SENDMSG(tag, destination, length);

```
Arguments:
int tag;
int destination;
int length;
```

TAU_TRACE_SENDMSG traces an inter-process message communication when a tagged message is sent to a destination process.

TAU_TRACE_RECVMSG(tag, source, length);

```
Arguments:
int tag;
int source;
int length;
```

TAU_TRACE_RECVMSG traces a receive operation where tag represents the type of the message received from the source process.

Example:

```
if (pid == 0){
  TAU_TRACE_SENDMSG(currCol, sender, ncols * sizeof(T));
  MPI_Send(vctr2, ncols * sizeof(T), MPI_BYTE, sender,
     currCol, MPI_COMM_WORLD);
} else {
  MPI_Recv(&ans, sizeof(T), MPI_BYTE, MPI_ANY_SOURCE,
     MPI_ANY_TAG,MPI_COMM_WORLD, &stat);
  MPI_Get_count(&stat, MPI_BYTE, &recvcount);
  TAU_TRACE_RECVMSG(stat.MPI_TAG, stat.MPI_SOURCE,
     recvcount);
}
```

TAU Mapping API

TAU allows the user to map performance data of entities from one layer to another in a multi-layered software. Mapping is used in profiling (and tracing) both synchronous and asynchronous models of computation. For mapping, the following macros are used. First locate and identify the higher-level statement using the `TAU_MAPPING` macro. Then, associate a function identifier with it using the `TAU_MAPPING_OBJECT`. Associate the high level statement to a FunctionInfo object that will be visible to lower level code, using `TAU_MAPPING_LINK`, and then profile entire blocks using `TAU_MAPPING_PROFILE`. Independent sets of statements can be profiled using `TAU_MAPPING_PROFILE_TIMER` and `TAU_MAPPING_PROFILE_START` and `TAU_MAPPING_PROFILE_STOP` macros using the FunctionInfo object.

TAU_MAPPING(statement, key);

```
Arguments:
statement ; // any C++ statement
TauGroup_t key; // TAU group/unique key associated
```

`TAU_MAPPING` is used to encapsulate the C++ statement that we want to map to some other layer. The other layer can execute synchronously or asynchronously with respect to this statement. The key corresponds to a number that the lower layer will use to refer to this statement. For example,

```
int main()
{
  Array <2> A(N, N), B(N, N), C(N,N), D(N, N);
  //Original statement:
  A = B + C + D;
  //Instrumented statement:
  TAU_MAPPING(A = B + C + D; , TAU_USER);
...
}
```

TAU_MAPPING_CREATE(name, type, key, groupname, tid);

```
Arguments:
char *name, type, groupname;
TauGroup_t key; // TAU group/unique key associated
int tid; // Thread id
```

TAU_MAPPING_CREATE is similar to TAU_MAPPING but it requires the name, type and group name parameters (as character strings) to be specified. It creates a mapping and associates it with the key that is specified. Later, this key may be specified to retrieve the FunctionInfo object associated with this key for timing purposes. The thread identifier is specified in the tid parameter.

For example:

```
TAU_MAPPING_CREATE("foo()", "void ()",
function_id,"USER", tid);
```

TAU_MAPPING_OBJECT(FuncIdVar);

```
Arguments: FunctionInfo *FuncIdVar;
```

To create storage for an identifier associated with a higher level statement that is mapped using TAU_MAPPING, we use the TAU_MAPPING_OBJECT macro. For example, in the TAU_MAPPING example, the array expressions are created into objects of a class ExpressionKernel, and each statement is an object that is an instance of this class. To embed the identity of the statement we store the mapping object in a data field in this class. This is shown below:

```
 template<class LHS,class Op,class RHS,class EvalTag>
class ExpressionKernel : public Pooma::Iterate_t
{
public:

  typedef ExpressionKernel<LHS,Op,RHS,EvalTag> This_t;
  //
  // Construct from an Expr.
```

```
  // Build the kernel that will evaluate the expression
on the given domain.
  // Acquire locks on the data referred to by the
expression.
  //
  ExpressionKernel(const LHS&,const Op&,const
RHS&,Pooma::Scheduler_t&);


  virtual ~ExpressionKernel();

  //
  // Do the loop.
  //
  virtual void run();

private:

  // The expression we will evaluate.
  LHS lhs_m;
  Op  op_m;
  RHS rhs_m;
  TAU_MAPPING_OBJECT(TauMapFI)
};
```

TAU_MAPPING_LINK(FuncIdVar, Key);

```
Arguments: FunctionInfo *FuncIdVar;
TauGroup_t Key;
```

TAU_MAPPING_LINK creates a link between the object defined in TAU_MAPPING_OBJECT (that identifies a statement) and the actual higher-level statement that is mapped with TAU_MAPPING. The Key argument represents a profile group to which the statement belongs, as specified in the TAU_MAPPING macro argument. For the example of array statements, this link should be created in the constructor of the class that represents the expression. TAU_MAPPING_LINK should be executed before any measurement takes place. It assigns the identifier of the statement to the object to which FuncIdVar refers. For e.g.:

```
//
// Constructor
// Input an expression and record it for later use.
//
template<class LHS,class Op,class RHS,class EvalTag>
ExpressionKernel<LHS,Op,RHS,EvalTag>::
ExpressionKernel(const LHS& lhs,const Op& op,const
    RHS&  rhs,      Pooma::Scheduler_t& scheduler) :
    Pooma::Iterate_t(scheduler,        forEachTag(Make-
    Expression<LHS>::make(lhs),  DataBlockTag<Count-
    Blocks>(),SumCombineTag()) +
    forEachTag(MakeExpression<RHS>::make(rhs), Dat-
    aBlockTag<CountBlocks>(),SumCombineTag()), -1),
   lhs_m(lhs), op_m(op), rhs_m(rhs)
{
  TAU_MAPPING_LINK(TauMapFI, TAU_USER)
// .. rest of the constructor
}
```

TAU_MAPPING_PROFILE (FuncIdVar);

```
Arguments; FunctionInfo *FuncIdVar;
```

The TAU_MAPPING_PROFILE macro measures the time and attributes it to the statement mapped in TAU_MAPPING macro. It takes as its argument the identifier of the higher level statement that is stored using TAU_MAPPING_OBJECT and linked to the statement using TAU_MAPPING_LINK macros. TAU_MAPPING_PROFILE measures the time spent in the entire block in which it is invoked. For example, if the time spent in the run method of the class does work that must be associated with the higher-level array expression, then, we can instrument it as follows:

```
//
// Evaluate the kernel
// Just tell an InlineEvaluator to do it.
//

template<class LHS,class Op,class RHS,class EvalTag>
void
```

```
ExpressionKernel<LHS,Op,RHS,EvalTag>::run()
{
  TAU_MAPPING_PROFILE(TauMapFI)

  // Just evaluate the expression.
  KernelEvaluator<EvalTag>().evalate(lhs_m,op_m,rhs_m);
  // we could release the locks here or in dtor
}
```

TAU_MAPPING_PROFILE_TIMER(timer, FuncIdVar);

```
Arguments: Profiler timer;
FunctionInfo * FuncIdVar;
```

TAU_MAPPING_PROFILE_TIMER enables timing of individual statements, instead of complete blocks. It will attribute the time to a higher-level statement. The second argument is the identifier of the statement that is obtained after TAU_MAPPING_OBJECT and TAU_MAPPING_LINK have executed. The timer argument in this macro is any variable that is used subsequently to start and stop the timer.

TAU_MAPPING_PROFILE_START(timer, tid);

```
Argument:
Profiler timer;
int tid;
```

TAU_MAPPING_PROFILE_START starts the timer that is created using TAU_MAPPING_PROFILE_TIMER. This will measure the elapsed time in groups of statements, instead of the entire block. A corresponding stop statement stops the timer as described next. The thread identifier is specified in the tid parameter.

TAU_MAPPING_PROFILE_STOP(tid);

```
Arguments:
int tid;
```

TAU_MAPPING_PROFILE_STOP stops the timer associated with the mapped lower-level statements. This is used in conjunction with TAU_MAPPING_PROFILE_TIMER and TAU_MAPPING_PROFILE_START macros. For example:

```
template<class LHS,class Op,class RHS,class EvalTag>
void
ExpressionKernel<LHS,Op,RHS,EvalTag>::run()
{
  TAU_MAPPING_PROFILE_TIMER(timer, TauMapFI);
  printf("ExpressionKernel::run() this = %x\n", this);
  // Just evaluate the expression.

  TAU_MAPPING_PROFILE_START(timer);
      KernelEvaluator<EvalTag>().evaluate(lhs_m, op_m,
          rhs_m);
  TAU_MAPPING_PROFILE_STOP();
  // we could release the locks here instead of in the
dtor.
}
```

This concludes our Mapping section.

C Instrumentation API

The API for instrumenting C source code is similar to the C++ API. The difference is that `the TAU_PROFILE()` macro is not available for identifying an entire block of code or function. Instead, routine transitions are explicitly specified using `TAU_PROFILE_TIMER()` macro with `TAU_PROFILE_START()` and `TAU_PROFILE_STOP()` macros to indicate the entry and exit from a routine.

Note that, TAU_TYPE_STRING() and CT() macros are not applicable for C. It is important to declare the TAU_PROFILE_TIMER() macro after all the variables have been declared in the function and before the execution of the first C statement.

Example:

```
int main (int argc, char **argv)
{
  int ret;
  pthread_attr_t  attr;
  pthread_t       tid;
  TAU_PROFILE_TIMER(tautimer,"main()", "int (int, char
     **)", TAU_DEFAULT);
  TAU_PROFILE_START(tautimer);
  TAU_PROFILE_INIT(argc, argv);
  TAU_PROFILE_SET_NODE(0);

  pthread_attr_init(&attr);
  printf("Started Main...\n");
  // other statements
  TAU_PROFILE_STOP(tautimer);
  return 0;
}
```

Fortran90 Instrumentation API

The Fortran90 TAU API allows source code written in Fortran to be instrumented for TAU. This API comprises of Fortran routines. As explained in Chapter 2, the instrumentation can be disabled in the program by using on the link command line, the TAU stub makefile variable TAU_DISABLE. This points to a library that contains empty TAU instrumentation routines.

TAU_PROFILE_INIT()

TAU_PROFILE_INIT routine must be called before any other TAU instrumentation routines. It is called once, in the top level routine (program). It initializes the TAU library.

For example:

```
PROGRAM SUM_OF_CUBES
integer profiler(2)
save profiler

 call TAU_PROFILE_INIT()
```

TAU_PROFILE_TIMER(profiler, name)

```
Arguments:
integer profiler(2)
character name(size)
```

To profile a block of Fortran code, such as a function, subroutine, loop..., the user must first declare a profiler, which is an integer array of two elements (pointer) with the save attribute, and pass it as the first parameter to the TAU_PROFILE_TIMER subroutine. The second parameter must contain the name of the routine, which is enclosed in a single quote. TAU_PROFILE_TIMER declares the profiler that must be used to profile a block of code. The profiler is used to profile the statements using TAU_PROFILE_START and TAU_PROFILE_STOP as explained later. For example:

```
subroutine bcast_inputs
implicit none
integer profiler(2)
save profiler

include 'mpinpb.h'
include 'applu.incl'

integer IERR

call TAU_PROFILE_TIMER(profiler, 'bcast_inputs')
```

TAU_PROFILE_START(profiler)

```
Arguments:
```

```
integer profiler(2)
```

TAU_PROFILE_START starts the timer for profiling a set of statements. The timer (or the profiler) must be declared using TAU_PROFILE_TIMER routine, prior to using TAU_PROFILE_START.

TAU_PROFILE_STOP(profiler)

```
Arguments:
integer profiler(2)
```

TAU_PROFILE_STOP stops the timer used to profile a set of statements. It is used in conjunction with TAU_PROFILE_TIMER and TAU_PROFILE_START subroutines.

For example:

```
subroutine setbv
implicit none

include 'applu.incl'
c---------------------------------------------------
c   local variables
c---------------------------------------------------
integer profiler(2)
save profiler
integer i, j, k
integer iglob, jglob

      call TAU_PROFILE_TIMER(profiler, 'setbv')
      call TAU_PROFILE_START(profiler)
c   set the dependent variable values along the top and
c   bottom faces
      do j = 1, ny
         jglob = jpt + j
         do i = 1, nx
           iglob = ipt + i
```

```
            call exact( iglob, jglob, 1, u( 1, i, j, 1 )
)
            call exact( iglob, jglob, nz, u( 1, i, j, nz
) )
         end do
      end do
      call TAU_PROFILE_STOP(profiler)
      return
      end
```

TAU_PROFILE_SET_NODE(myNode)

```
Arguments:
integer myNode
```

The TAU_PROFILE_SET_NODE macro sets the node identifier of the executing task for profiling and tracing. TAU uses the HPC++ model of computation, where the tasks are identified using node, context and thread. The profile data files generated will accordingly be named
profile.<node>.<context>.<thread>.

TAU_PROFILE_SET_CONTEXT(myContext)

```
Argument:
integer myContext
```

TAU_PROFILE_SET_CONTEXT sets the context parameter of the executing task for profiling and tracing purposes. This is similar to setting the node parameter with TAU_PROFILE_SET_NODE.

TAU_PROFILE_REGISTER_THREAD()

To register a thread with the profiling system, invoke the TAU_PROFILE_REGISTER_THREAD routine in the run method of the thread

prior to executing any other TAU routine. This sets up thread identifiers that are later used by the instrumentation system.

TAU_PROFILE_EXIT(message)

```
Argument:
character message(size)
```

TAU_PROFILE_EXIT should be called prior to an error exit from the program so that any profiles or event traces can be dumped to disk before quitting.

Example:

```
call TAU_PROFILE_EXIT('abort called')
```

TAU_REGISTER_EVENT(variable, event_name)

```
Arguments:
int variable(2)
character event_name(size)
```

TAU can profile user-defined events using TAU_REGISTER_EVENT. The meaning of the event is determined by the user. The first argument to TAU_REGISTER_EVENT is the pointer to an integer array. This array is declared with a save attribute as shown below.

Example:

```
integer eventid(2)
save eventid
call TAU_REGISTER_EVENT(eventid, 'Error in Iteration')
```

TAU_EVENT(variable, value)

```
Arguments:
integer variable(2)
```

```
real value
```

TAU_EVENT associates a value with some user-defined event. When the event is triggered and this macro is executed, TAU maintains statistics, such as maximum, minimum values, standard deviation, number of samples, etc. for tracking this event.

Example:

```
call TAU_REGISTER_EVENT(taumsgsize, 'Message size')
call TAU_EVENT(size)
```

TAU_REPORT_STATISTICS()

TAU_REPORT_STATISTICS prints the aggregate statistics of user events across all threads in each node. Typically, this should be called just before the main thread exits.

TAU_REPORT_THREAD_STATISTICS()

TAU_REPORT_THREAD_STATISTICS prints the aggregate, as well as per thread user event statistics. Typically, this should be called just before the main thread exits.

TAU_TRACE_SENDMSG(tag, destination, length)

```
Arguments:
integer tag
integer destination
integer length
```

TAU_TRACE_SENDMSG traces an inter-process message communication when a tagged message is sent to a destination process.

TAU_TRACE_RECVMSG(tag, source, length)

```
Arguments:
integer tag
integer source
integer length
```

TAU_TRACE_RECVMSG traces a receive operation where tag represents the type of the message received from the source process.

Summary

In C++, a single macro viz., TAU_PROFILE, is sufficient to profile a block of statements. In C, and Fortran the user must use statement level timers to achieve this, using TAU_PROFILE_TIMER, TAU_PROFILE_START and TAU_PROFILE_STOP. Instrumentation of C++ source code can be done manually or by using tau_instrumentor, a tool that can automatically insert TAU annotations in the source code. We are working on a Fortran 90 instrumentor, which should be available in the near future.

CHAPTER 4

Profiling

This chapter describes running of an instrumented application and generation and subsequent analysis of profile data. Profiling shows the summary statistics of performance metrics that characterize the performance of an application. Examples of performance metrics are the CPU time associated with a routine, the count of the secondary data cache misses associated with a group of statements, the number of times a routine executes, etc.

Running the application

After instrumentation and compilation are completed, the profiled application is run to generate the profile data files. These files can be stored in a directory specified by the environment variable PROFILEDIR as explained in Chapter 2. By default, all instrumented routines and statements are measured. To selectively measure groups of routines and statements, we can use the command-line parameter `--profile` to specify the statements to be profiled. For example:

```
% setenv PROFILEDIR /home/sameer/profiledata/
experiment55
% mpirun -np 4 matrix
```

This profiles all routines

```
% mpirun -np 4 matrix --profile io+field+2
```

The above profiles routines belonging to `TAU_IO`, `TAU_FIELD` and `TAU_USER2` profile groups. For a detailed list of groups, please refer to
URL: `http://www.acl.lanl.gov/tau` (Docs->Tutorial->Selective Profiling section)

Java Applications are profiled/traced using the -XrunTAU commandline parameter as shown below:

```
% setenv LD_LIBRARY_PATH $LD_LIBRARY_PATH:/home/tau/
solaris2/lib
% java -XrunTAU Pi
or
% java -XrunTAU -Djava.compiler=  Pi
To disable the JIT compiler.
```

Running the application generates profile files with names having the form profile.<node>.<context>.<thread>. These files can be analyzed using pprof or racy.

Using Hardware Performance Counters

Performance counters exist on modern microprocessors. These count hardware performance events such as cache misses, floating point operations, etc. while the program executes on the processor. Performance Counter Library (PCL,

URL:`http://www.fz-juelich.de/zam/PCL/`) package provides a uniform interface to access these performance counters. TAU uses PCL to access these hardware performance counters. To use PCL, download and install PCL. Then, configure TAU using the -pcl=<dir> configuration command-line option to specify the location of PCL. Build TAU and applications as you normally would (as described in Chapters 2 and 3). While running the application, set the environment variable `PCL_EVENT` to specify which hardware performance counter TAU should use while profiling the application. For example to measure the floating point operations in routines,

```
% ./configure -pcl=/usr/local/packages/pcl-1.2
% setenv PCL_EVENT PCL_FP_INSTR
% mpirun -np 8 application
```

TABLE 1. Events measured by setting the environment variable `PCL_EVENT` in TAU

PCL_EVENT	Event Measured
PCL_L1CACHE_READ	L1 (Level one) cache reads
PCL_L1CACHE_WRITE	L1 cache writes
PCL_L1CACHE_READWRITE	L1 cache reads and writes
PCL_L1CACHE_HIT	L1 cache hits
PCL_L1CACHE_MISS	L1 cache misses
PCL_L1DCACHE_READ	L1 data cache reads
PCL_L1DCACHE_WRITE	L1 data cache writes
PCL_L1DCACHE_READWRITE	L1 data cache reads and writes
PCL_L1DCACHE_HIT	L1 data cache hits
PCL_L1DCACHE_MISS	L1 data cache misses
PCL_L1ICACHE_READ	L1 instruction cache reads
PCL_L1ICACHE_WRITE	L1 instruction cache writes
PCL_L1ICACHE_READWRITE	L1 instruction cache reads and writes
PCL_L1ICACHE_HIT	L1 instruction cache hits
PCL_L1ICACHE_MISS	L1 instruction cache misses
PCL_L2CACHE_READ	L2 (Level two) cache reads
PCL_L2CACHE_WRITE	L2 cache writes
PCL_L2CACHE_READWRITE	L2 cache reads and writes
PCL_L2CACHE_HIT	L2 cache hits

TABLE 1. Events measured by setting the environment variable `PCL_EVENT` in TAU

PCL_EVENT	Event Measured
PCL_L2CACHE_MISS	L2 cache misses
PCL_L2DCACHE_READ	L2 data cache reads
PCL_L2DCACHE_WRITE	L2 data cache writes
PCL_L2DCACHE_READWRITE	L2 data cache reads and writes
PCL_L2DCACHE_HIT	L2 data cache hits
PCL_L2DCACHE_MISS	L2 data cache misses
PCL_L2ICACHE_READ	L2 instruction cache reads
PCL_L2ICACHE_WRITE	L2 instruction cache writes
PCL_L2ICACHE_READWRITE	L2 instruction cache reads and writes
PCL_L2ICACHE_HIT	L2 instruction cache hits
PCL_L2ICACHE_MISS	L2 instruction cache misses
PCL_TLB_HIT	TLB (Translation Lookaside Buffer) hits
PCL_TLB_MISS	TLB misses
PCL_ITLB_HIT	Instruction TLB hits
PCL_ITLB_MISS	Instruction TLB misses
PCL_DTLB_HIT	Data TLB hits
PCL_DTLB_MISS	Data TLB misses
PCL_CYCLES	Cycles
PCL_ELAPSED_CYCLES	Cycles elapsed
PCL_INTEGER_INSTR	Integer instructions executed
PCL_FP_INSTR	Floating point (FP) instructions executed
PCL_LOAD_INSTR	Load instructions executed
PCL_STORE_INSTR	Store instructions executed
PCL_LOADSTORE_INSTR	Loads and stores executed
PCL_INSTR	Instructions executed
PCL_JUMP_SUCCESS	Successful jumps executed
PCL_JUMP_UNSUCCESS	Unsuccessful jumps executed
PCL_JUMP	Jumps executed
PCL_ATOMIC_SUCCESS	Successful atomic instructions executed

TABLE 1. Events measured by setting the environment variable `PCL_EVENT` in TAU

PCL_EVENT	Event Measured
PCL_ATOMIC_UNSUCCESS	Unsuccessful atomic instructions executed
PCL_ATOMIC	Atomic instructions executed
PCL_STALL_INTEGER	Integer stalls
PCL_STALL_FP	Floating point stalls
PCL_STALL_JUMP	Jump stalls
PCL_STALL_LOAD	Load stalls
PCL_STALL_STORE	Store Stalls
PCL_STALL	Stalls
PCL_MFLOPS	Milions of floating point operations/second
PCL_IPC	Instructions executed per cycle
PCL_L1DCACHE_MISSRATE	Level 1 data cache miss rate
PCL_L2DCACHE_MISSRATE	Level 2 data cache miss rate
PCL_MEM_FP_RATIO	Ratio of memory accesses to FP operations

pprof

pprof sorts and displays profile data generated by TAU. To view the profile, merely execute pprof in the directory where profile files are located (or set the `PROFILEDIR` environment variable).

```
% pprof
```

Its usage is explained below:

```
usage: pprof [-c|-b|-m|-t|-e|-i] [-r] [-s] [-n num] [-f
filename] [-l] [node numbers]
  -c : Sort by number of Calls
  -b : Sort by number of suBroutines called by a func-
tion
  -m : Sort by Milliseconds (exclusive time total)
  -t : Sort by Total milliseconds (inclusive time total)
(DEFAULT)
  -e : Sort by Exclusive time per call (msec/call)
```

```
  -i : Sort by Inclusive time per call (total msec/call)
  -v : Sort by standard deViation (excl usec)
  -r : Reverse sorting order
  -s : print only Summary profile information
  -n num : print only first num functions
  -f filename : specify full path and Filename without
node ids
  -l : List all functions and exit
 [node numbers] : prints information about all contexts/
threads for specified nodes
```



FIGURE 1. pprof in an xemacs window

racy

Racy is the graphical interface to pprof. It shows the profile data in terms of histograms and text displays. Invoke racy in the directory that contains the profile files.

```
% racy
```

In the project management window, select a project by typing in a project file name with a .pmf extension (e.g., `matrix.pmf`), and clicking (the first mouse button) on the "`Create`" button.



FIGURE 2. Create a project by creating or choosing an existing project

NOTE: If the project window does not appear, it is probably due to problems with the security of the X-display. You may not use `xhost +` while using racy. You may need to explicitly turn off xhost by invoking `xhost -` and using Xauthentication. The cookies are generated and stored in the `~/.Xauthority` file. If your server is not configured to generate these cookies, please contact your system administrator for configuring the X display to make it secure. Users may also want

to use **ssh**, rather than telnet/rlogin to login to a remote node where racy is invoked. If this is done, the cookies need not be copied to the remote node explicitly by the user. For more information please refer to :

URL: `http://www.acl.lanl.gov/tau/docs/faq.html#security`

After the project is created or selected, the main racy window appears.



FIGURE 3. Main racy window showing the profile of functions on different <node>,<context>,<thread>s and the mean profile.

This shows the relative time spent in each function as a horizontal bargraph. Each node, context, thread is represented as a horizontal bar with each function assigned a color. In this main racy window, click middle mouse button over n,c,t 0,0,0 to see the textual profile of node 0, context 0, thread 0.



FIGURE 4. Text shows the detailed profile on n,c,t 0,0,0.

Next, select Show Function Legend on the main racy window File menu to see the list of functions.



FIGURE 5. The Function Legend window shows the color assigned to each function.

Click the third mouse button over a function to highlight it in the currently open windows. To see the relative function profile on one node, click first mouse button on a node in the racy main window.



FIGURE 6. The above node profile shows the relative contribution of the functions on the node 0, context 0, thread 0 .

Click, using the first or the third mouse button, on the name of a function to bring up the function window that shows the profile of the function over all nodes, contexts and threads.



FIGURE 7. The function window shows the profile of the function over all nodes, contexts and threads.

If user-defined events are profiled in addition to routines, then an event window appears with the function profile window. Navigation of user event profiles is identical to the navigation of function profiles as described above. The following figure demonstrates the use of user-defined event profiles from the PaRP project (URL: `http://www.csi.uoregon.edu/parp`)



FIGURE 8. Racy displays user defined event profiles as well.

User defined events are also measured and displayed on each node, context and thread.



FIGURE 9. User defined events may be used to track memory bugs.

CHAPTER 5

Tracing

This chapter discusses how TAU can be used to generate event traces.

Typically, profiling shows the distribution of execution time across routines. It can show the code locations associated with specific bottlenecks, but it does not show the temporal aspect of performance variations. Tracing the execution of a parallel program shows when and where an event occured, in terms of the process that executed it and the location in the source code.

Generating Event Traces

TAU must be configured with the -TRACE option to generate event traces. This can be used in conjunction with -PROFILE to generate both profiles and traces. The traces are stored in a directory specified by the environment variable TRACEDIR, or the current directory, by default. For example:

```
% ./configure -SGITIMERS -arch=sgi64 -TRACE  -c++=KCC
% make clean; make install
% setenv TRACEDIR /users/sameer/tracedata/experiment56
% mpirun -np 4 matrix
```

This generates files named

`tautrace.<node>.<context>.<thread>.trc` and
`events.<node>.edf`

Using the utility **`tau_merge`**, these traces are then merged as shown below:

```
% tau_merge
usage: tau_merge [-a] [-r] inputtraces* (outputtrace|-)
Note: tau_merge assumes edf files are named
events.<nodeid>.edf, and generates a merged edf file
tau.edf
% tau_merge tautrace*.trc matrix.trc
```

This generates matrix.trc as the merged trace file and tau.edf as the merged event description file.

To convert merged or per-thread traces to another trace format, the utility **`tau_convert`** is used as shown below:

```
% tau_convert
usage: tau_convert [-alog | -SDDF | -dump | -pv | -vam-
pir [-compact] [-user|-class|-all] [-nocomm]] inputtrc
edffile [outputtrc]
 Note: -vampir option assumes multiple threads/node
```

To view the dump of the trace in text form, use

```
% tau_convert -dump matrix.trc tau.edf
```

tau_convert can also be used to convert traces to the Vampir trace format (URL: `http://www.pallas.de`). For single-threaded applications (such as the MPI application above), the `-pv` option is used to generate Vampir traces as follows:

```
% tau_convert -pv matrix.trc tau.edf matrix.pv
% vampir matrix.pv &
```

When multiple threads are used on a node (as with -jdk, -pthread or -tulipthread options during configure), the `-vampir` option is used to convert the traces to the vampir trace format, as shown below:

```
% tau_convert -vampir smartsapp.trc tau.edf smartsapp.pv
% vampir smartsapp.pv &
```

NOTE: To ensure that inter-process communication events are recorded in the traces, in addition to the routine transitions, it is necessary to insert TAU_TRACE_SENDMSG and TAU_TRACE_RECVMSG macro calls in the source code during instrumentation. This is not needed when the TAU MPI Wrapper library is used.

Vampir: Visualizing TAU traces

This describes the types of visualizations of trace data that Vampir provides. Event traces can show, using a global timeline display, when routine transitions take place on different processes.



FIGURE 10. Vampir displays space-time diagrams and pie-charts

When interprocess communication is recorded, it shows up as directed line-segments connecting the sending and receiving processes. The details of a message can be obtained by clicking on it:



FIGURE 11. Vampir Space-time diagram shows inter-process communication

Vampir is used to display scheduling of work packets or iterates in SMARTS, the Shared Memory Asynchronous Runtime System (`URL: http://www.acl.lanl.gov/smarts`):



FIGURE 12. Scheduling work packets in SMARTS

In the next figure, we see the symbol legend and the dynamic call tree.



FIGURE 13. Vampir symbol legend and calltree display

Vampir has been used to compare the scheduling policies of the SMARTS package.



FIGURE 14. Comparing scheduling policies in SMARTS

The following figures illustrate the use of Vampir with Java applications. After converting the traces and invoking Vampir, choose appropriate colors for groups of methods using `Preferences-> Colors->Activities` menu in Vampir.



FIGURE 15. Timeline display in Vampir shows the activity (method) that each thread is in wrt time.

Clicking on a process(thread) selects it. Then the user can see the dynamic call tree of the process by choosing the `Process Displays -> Call Tree` menu item as shown below.



FIGURE 16. Call tree display of a thread shows the dynamic call tree annotated with performance metrics.

Vampir has a rich set of global displays. By choosing the `Global Displays -> Parallelism View` the user can see how many threads participate in an activity belonging to a group at any point in time. All timeline displays support a zoom option where the user can zoom into or out of a section of the trace.



FIGURE 17. Parallelism view

By choosing other global displays such as Summaric chart or activity chart, the user can see a global summary of the time spent in different groups of methods as shown in the following figure.



FIGURE 18. Summaric chart and activity chart global displays highlight the groups that take the most time using pie charts and histograms respectively.

CHAPTER 6 *Summary*

This chapter discusses the availability of the software and related issues.

Software Availability

TAU Portable Profiling and Tracing Toolkit may be downloaded as freeware from the following website:

`http://www.acl.lanl.gov/tau`

TAU was also released on the ACL Fall 1998 CD-ROM available from :

`http://www.acl.lanl.gov/software`

For more information, please refer to the documentation section at the above URL. Bug reports and comments may be sent to :

`tau-bugs@cs.uoregon.edu`

Technical papers about TAU can be downloaded from the TAU Publications home-page at:

`http://www.cs.uoregon.edu/research/paracomp/tau/papers.html`

Acknowledgements

The TAU development team wishes to thank the U.S. Government, Department of Energy for their support of the TAU project under the DOE-2000 and LANL ASCI Level 3 grants.